

Lampiran 1 : Prosedur Program

```

[*****]
{     Nama      : SAFRUDIN          }
{     NIM       : J2D096176         }
{   Jurusan: Fisika            }
{   FMIPA Universitas Diponegoro  }
{           Semarang           }
[*****]

Program penguatanautomatik;
Uses dos, Crt, graph;
type da= array[0..10,0..640] of byte;
pp= array[0..6] of byte;
Aap= array[0..6] of real;
Vvp= array[0..3200] of integer;

Var
  z,tegref,V,Vmak,Vmin,Vm,Volt,TTrat,frat,fmak,fmin,fW,konfer,
  Tmak,Tmin,Trat,Vef,Vrat,sum,sumef,vma,vmi,Vdc : real;
  N, m, k, j, x, a, b, c, i, grafdrv, grafmode,DP,DPP,IX,IOX,
  IOOX,IOOOX,peri,per20,per200,ke,TTmak,TTmin,cacah,fa,pe,kt
  : integer;
  y, yt, yr, auto,auti,manual,pilih1,nol :byte;
  simpan :text;
  ys, yc : da;
  p : pp;
  Ap,Vp : Aap;
  Vi,Vj,Vpi,Vpj,TT    :Vvp;

procedure pilih_skala;
Begin
  clrscr; tegref:=5.02; Vma:=-500; Vmi:=500;
  IX:=6; IOX:=4; IOOX:=2; IOOOX:=0;
  peri:=24; per20:=8; per200:=0;
  DP:=per200+IX;
  port[$378]:=DP;
  DPP:=DP+1;
  p[0]:=per200+IX;p[1]:=per20+IX;p[2]:=per20+IOX;p[3]:=peri+IX;
  p[4]:=peri+IOX;p[5]:=peri+IOOX;p[6]:=peri+IOOOX;
  Ap[0]:=1/200;Ap[1]:=1/20;Ap[2]:=1/2;Ap[3]:=1;Ap[4]:=10;Ap[5]:=100;Ap[6]:=1000;
  manual:=0;
  writeln(' Petunjuk skala pelemahan dan Penguatan');
  writeln(' Pilih (tekan tombol) angka sebagai berikut');
  writeln(' Angka/Tombol = Skala');
  writeln(' 0 = -500 Volt sampai +500 Volt');
  writeln(' 1 = -50 Volt sampai +50 Volt');
  writeln(' 2 = -5 Volt sampai +5 Volt');
  writeln(' 3 = -2,5 Volt sampai +2,5 Volt');
  writeln(' 4 = -250 mVolt sampai +250 mVolt');
  writeln(' 5 = -25 mVolt sampai +25 mVolt');
  writeln(' 6 = -2,5 mVolt sampai +2,5 mVolt');
  readln(manual);
  DP:=p[manual];
  port[$378]:=DP;
  DPP:=DP+1;
  delay(2000);

```

```

for i:=0 to 10 do
begin
port[$378]:=DP;
for m:=0 to 1 do n:=m;
m:=n;
yt:=port[$379];
ys[1,i]:=yt;
yr:=port[$37A];
yc[1,i]:=yr;
port[$378]:=DPP;
for m:=0 to 1700 do n:=m; {delay jangan lebih kecil 1700}
end;
for i:=0 to 10 do
begin
y:= ys[1,i] + yc[1,i] - 239;
V:=(y-nol)/255)*tegref;
Volt:=V/ap[manual];
if Volt>Vma then Vma:=Volt;
if volt<Vmi then Vmi:=Volt;
end;
if sqrt(sqr(Vmi))>Vma then Vma:=sqrt(sqr(Vmi));
I:=1;
while (V>2.5) and (I=1) do
begin
I:=2;
DP:=p[0];
port[$378]:=DP;
writeln(' gagal = tidak sesuai skala');
readin;
end;
writeln('Vmaksimum=',Vma);
writeln('Vminimun=',Vmi);
delay(1000);
auto:=manual;
end;

Procedure port_ke_memory;
Begin
for j:=0 to 10 do
begin
for i:=0 to 640 do
begin
port[$378]:=DP;
for m:=0 to 1 do n:=m;
m:=n;
yt:=port[$379];
ys[j,i]:=yt;
yr:=port[$37A];
yc[j,i]:=yr;
port[$378]:=DPP;
for m:=0 to 1700 do n:=m; {delay jangan lebih kecil 1700}
end;
end;
End;

Procedure tampilan;
Begin
grafdrv :=detect;
InitGraph(grafdrv,grafmode,' ');
for j:=0 to 10 do
begin
cleardevice;
line(0,nol,640,nol);

```

```

line(0,256,640,256);
line(320,0,320,256);
for i:=0 to 640 do
begin
y:= ys[j,i] + yc[j,i] - 239;
delay (1);
putpixel(i,y,3);
end;
end;
Procedure puncak;
begin
Vmak:=-500;
Vmin:=500;
Vdc:=0;
ke:=0;
m:=1;n:=0;
for j:=0 to 10 do
begin
for i:=0 to 640 do
begin
n:=1;
y:= ys[j,i] + yc[j,i] - 239;
if j=10 then Vdc:=Vdc+y;
while (y>=(Vmak-(Vmak/20))) and (n=1) do
begin
n:=2;
Vi[m]:=i;
Vj[m]:=j;
if y>Vmak then Vmak:=y;
m:=m+1;
if m>=1500 then Vmak:=-500;
if m>=3200 then m:=0;
end;
if y<Vmin then Vmin:=y;
end;
End;
Vma:=-500;
for i:=0 to m-1 do
begin
n:=2;
y:= ys[Vj[i],Vi[i]] + yc[Vj[i],Vi[i]] - 239;
if y>vma then vma:=y;
while ((Vi[i]-Vi[i-1])>5) and (n=2) do
begin
n:=3;
Vp[ke]:=vma;
Vpi[ke]:=Vi[i];
Vpj[ke]:=Vj[i];
ke:=ke+1;
Vma:=-500;
if ke>=320 then ke:=0;
end;
Vmak:=((nol-Vmak)/255)*tegref)/ap[auto];
Vmin:=((nol-Vmin)/255)*tegref)/ap[auto];
Vdc:=(((nol-(Vdc/645))/255)*tegref)-0)/ap[auto];
End;
Procedure perioda;
Begin
TTmin:=6400;

```

```

TTmak:=0;
TT[0]:=0;
TTrat:=0;
for m:=1 to ke-1 do
begin
  if Vpj[m]=Vpj[m-1] then TT[m]:=(Vpi[m]-Vpi[m-1]) ;
end;
J:=0;
for n:=4 to 'm do
begin
  i:=0;
  while (TT[n]>0) and (i=0) do
  begin
    i:=1;
    if TT[n]>=TTmak then TTmak:=TT[n];
    if TT[n]<=TTmin then TTmin:=TT[n];
    ttrat:=ttrat+TT[n];
  end;
  if TT[n]>3 then j:=j+1;
end;
if j=0 then j:=1;
TTrat:=ttrat/j;
End;

Procedure Konfersifrek;
Begin
Konfer:=6779.9;
frat:=((1/(TTrat+0.000001))*konfer)-0.5291;
fmak:=((1/(TTmak+0.000001))*konfer)-0.5291;
fmin:=((1/(TTmin+0.000001))*konfer)-0.5291;
Trat:=1/frat;Tmak:=1/fmak;Tmin:=1/fmin;
fW:=fmak-fmin;
end;

function fungsibode:string;
Begin
  case cacah of
    1: fa :=32;
    2: fa :=12;
    3: fa :=32;
    4: begin
        fa :=7;
        y:= ys[j,i] + yc[j,i] - 239;
        V:=((y-nol)/255)*tegref;
        sum := sum + (V*fa);
        sumef:= sumef + (sqr(V)*fa);
      end;
    end;
    y:= ys[j,i] + yc[j,i] - 239;
    V:=((y-nol)/255)*tegref;
    sum := sum + (V*fa);
    sumef:= sumef + (sqr(V)*fa);
    cacah:= cacah + 1;
    if(cacah=5) then cacah :=1;
  end;
End;

Procedure bode;
Begin
y:= ys[Vpj[ke-3],Vpi[ke-3]] + yc[Vpj[ke-3],Vpi[ke-3]] - 239;
V:=((y-nol)/255)*tegref;
sum:=(7.0*V);
sumef:=(7.0*sqr(V));

```

```

Vrat:=0;
Vef:=0;
Cacah:=1;
n:=0;
while (Vpj[ke-2]-Vpj[ke-3]=0) and (n=0) do
begin
n:=1;
j:=Vpj[ke-2];
for i:=(Vpi[ke-3]+1) to Vpi[ke-2] do fungsibode;
end;
while (Vpj[ke-2]-Vpj[ke-3]>0) and (n=0) do
begin
n:=2;
for j:=Vpj[ke-3] to Vpj[ke-2] do
begin
n:=3;
while (j<=Vpj[ke-3]) and (n=3) do
begin
n:=4;
for i:=(Vpi[ke-3]+1) to 640 do fungsibode;
end;
while (j>Vpj[ke-3]) and (n=3) do
begin
n:=5;
while (j<Vpj[ke-2]) and (n=5) do
begin
n:=6;
for i:=0 to 640 do fungsibode;
End;
end;
while (j>Vpj[ke-2]) and (n=3) do
begin
n:=7;
for i:=0 to (Vpi[ke-2]-1) do fungsibode;
end;
end;
End;
y:= ys[Vpj[ke-2],Vpi[ke-2]] + yc[Vpj[ke-2],Vpi[ke-2]] - 239;
V:=((y-nol)/255)*tegref;
sum := sum + (7.0*V);
sumef := sumef + (sqr(V)*fa);
sum := ((2.0*I)/45.0)*sum;
sumef := ((2.0*I)/45.0)*sumef;
pe:=(Vpi[ke-2]+((Vpj[ke-2]-Vpj[ke-3])*640)-Vpi[ke-3]);
if pe>0 then Vrat:=sum/pe;
Vrat:=-Vrat/ap[auto];
if pe>0 then Vef:=sqrt(sumef*I/(Pe));
Vef:=Vef/ap[auto];
end;

Procedure konfersiteg;
Begin
case auto of
0: begin
Vmak:= Vmak;
Vmin:= Vmin;
Vdc:= Vdc;
Vrat:= Vrat;
Vef:= Vef;
End;
1: begin
Vmak:= (1.1292*Vmak) -0.1333;
Vmin:= (1.1292*Vmin) -0.1333;

```

```

        Vdc:= (1.1292*Vdc) -0.1333;
        Vrat:= (1.1292*Vrat) -0.1333;
        Vef:= (1.1292*Vef) -0.1333;
    End;
2:begin
        Vmak:= (1.1209*Vmak) +0.0268;
        Vmin:= (1.1209*Vmin) +0.0268;
        Vdc:= (1.1209*Vdc) +0.0268;
        Vrat:= (1.1209*Vrat) +0.0268;
        Vef:= (1.1209*Vef) +0.0268;
    End;
3: begin
        Vmak:= (0.0212*Vmak*Vmak*Vmak) -
(0.0039*Vmak*Vmak)+(0.9616*Vmak)+0.0128;
        Vmin:= (0.0212*Vmin*Vmin*Vmin) -
(0.0039*Vmin*Vmin)+(0.9616*Vmin)+0.0128;
        Vdc:= (0.0212*Vdc*Vdc*Vdc) -
(0.0039*Vdc*Vdc)+(0.9616*Vdc)+0.0128;
        Vrat:= (0.0212*Vrat*Vrat*Vrat) -
(0.0039*Vrat*Vrat)+(0.9616*Vrat)+0.0128;
        Vef:= (0.0212*Vef*Vef*Vef) -
(0.0039*Vef*Vef)+(0.9616*Vef)+0.0128;
    End;
4: begin
        Vmak:= (1.0027*Vmak) -0.0001;
        Vmin:= (1.0027*Vmin) -0.0001;
        Vdc:= (1.0027*Vdc) -0.0001;
        Vrat:= (1.0027*Vrat) -0.0001;
        Vef:= (1.0027*Vef) -0.0001;
    End;
5: begin
        Vmak:= (1.0323*Vmak) +0.0007;
        Vmin:= (1.0323*Vmin) +0.0007;
        Vdc:= (1.0323*Vdc) +0.0007;
        Vrat:= (1.0323*Vrat) +0.0007;
        Vef:= (1.0323*Vef) +0.0007;
    End;
End;
End;

function intkestr(ii:integer):string;
var s:string[8];
begin
str(i,s);
intkestr:=s;
end;

function realkestr(rr:real):string;
var s:string[18];
begin
str(rr,s);
realkestr:=s;
end;

Procedure analisa;
Begin
outtextxy(5,280,'Tegangan Mak(Vdc)');
outtextxy(180,280,realkestr(vmin));
outtextxy(5,295,'Tegangan Min');
outtextxy(180,295,realkestr(vmak));
outtextxy(5,310,'Tegangan rata-rata(ac)');
outtextxy(180,310,realkestr(Vrat));
outtextxy(5,325,'TegDC rata-rata');

```

```

outtextxy(180,325,realkestr(Vdc));
outtextxy(5,340,'Tegangan efektif');
outtextxy(180,340,realkestr(Vef));
outtextxy(340,280,'Frekuensi Mak');
outtextxy(500,280,realkestr(fmak));
outtextxy(340,295,'Frekuensi Min');
outtextxy(500,295,realkestr(fmin));
outtextxy(340,310,'Frekuensi rata-rata');
outtextxy(500,310,realkestr(frat));
outtextxy(340,325,'Perioda Mak');
outtextxy(500,325,realkestr(Tmak));
outtextxy(340,340,'Perioda Min');
outtextxy(500,340,realkestr(Tmin));
outtextxy(340,355,'Perioda rata-rata');
outtextxy(500,355,realkestr(Trat));
End;

Procedure Save_A;
Begin
assign(simpan,'a:dat1.dat');
rewrite(simpan);
for j:=0 to 10 do
begin
for i:=0 to 640 do
begin
y:= ys[j,i] + yc[j,i] - 239;
writeln(simpan,y);
flush(simpan);
end;
end;
writeln(simpan,vmak);
flush(simpan);
writeln(simpan,vmin);
flush(simpan);
writeln(simpan,Vrat);
flush(simpan);
writeln(simpan,Vef);
flush(simpan);
writeln(simpan,Vdc);
flush(simpan);
writeln(simpan,fmak);
flush(simpan);
writeln(simpan,fmin);
flush(simpan);
writeln(simpan,frat);
flush(simpan);
writeln(simpan,Tmak);
flush(simpan);
writeln(simpan,Tmin);
flush(simpan);
writeln(simpan,Trat);
flush(simpan);
close(simpan);
end;

Procedure Baca_disk;
Begin
assign(simpan, 'a:dat1.dat');
reset(simpan);
grafdrv :=detect;
InitGraph(grafdrv,grafmode,' ');
for j:=0 to 10 do
begin

```



```

    cleardevice;
        cleardevice;
    line(0,nol,640,nol);
    line(0,256,640,256);
    line(320,0,320,256);
    for i:=0 to 640 do
    begin
    readln(simpan,y);
    delay(1);
    putpixel(i, y,3);
    end;
    end;
readln(simpan,vmak);
readln(simpan,vmin);
readln(simpan,Vrat);
readln(simpan,Vef);
readln(simpan,Vdc);
readln(simpan,fmak);
readln(simpan,fmin);
readln(simpan,frat);
readln(simpan,Tmak);
readln(simpan,Tmin);
readln(simpan,Trat);
close(simpan);
end;

{Program Utama}
Begin
nol:=128;
Clrscr;
writeln(' Selamat Menggunakan Program Penampil Sinyal');
writeln(' ');
writeln(' Pilih :');
writeln(' 1 = Tampilan Data Disket');
writeln(' 2 = Tampilan Sinyal Baru');
pilih1:=1;
write;
readln(pilih1);
while pilih1=1 do
begin
    clrscr;
    writeln(' Masukkan disket ke drive A (lalu tekan
enter)');
    Readln;
    writeln(' Sedang Baca Data');
    Baca_disk;
    analisa;
    pilih1:=0;
    readln;
end;
while pilih1=2 do
begin
    pilih_skala;
    delay(2000);
    port_ke_memory;
    DP:=per200+IX;
    port[$378]:=DP;
    puncak;
    Bode;
    perioda;
    konfersifrek;
    konfersiteg;


```

```
tampilan;
analisa;
readln;
closegraph;
clrscr;
write('    simpan data tekan 3 (bila tidak disimpan tekan 0)');
readln(pilih1);
if pilih1>2 then Save_A;
end;
end.
```




Lampiran 2 : Pengujian tegangan pada tiap skala untuk linierisasi


Skala	$V_r = V_t$ (V)	V_s (V)		
		min	mak	rata
3	-2.5	-2.30329	-2.2836	-2.293445
	-2	-1.968627	-1.948	-1.9583135
	-1.5	-1.51584	-1.49615	-1.505995
	-1	-1.023686	-9.84E-01	-1.0039996
	-0.493	-5.12E-01	-4.92E-01	-0.5019995
	-0.299	-3.15E-01	-2.95E-01	-0.305135
	0.311	2.95E-01	3.15E-01	0.304895
	0.501	4.72E-01	4.92E-01	0.48231
	1.008	9.84E-01	1.004	0.9941565
	1.5	1.47647	1.49615	1.48631
	2	1.948	1.96862	1.95831
	2.5	2.3032	2.32298	2.31309




Skala	$V_r = V_I$ (V)	V_s (V)		
		min	mak	rata
4	-0.234	-0.23426	-0.230329	-0.230751
	-0.1915	-0.19686	-0.1909	-0.19117
	-0.14985	-0.1555	-1.4764	-0.1499
	-0.0986	-0.104337	-0.098431	-0.099201
	-0.0257	-0.029529411	-0.0255921	-0.02577833
	0.285	0.0255921	0.02952	0.02755605
	0.1061	0.1023686	0.106305	0.1043368
	0.153	0.149615	0.15521	0.1524125
	0.202	0.202768	0.206705	0.2047365
	0.247	0.244109	0.248047	0.246078




Skala	$V_r = V_I$ (V)	V_s (V)		
		min	mak	rata
5	-0.0217	-0.0222454	-0.02087	-0.0219372
	-0.0149	-0.01693	-0.01437	-0.01625
	-0.0103	-0.011024	-0.00925254	-0.010582
	-0.0063	-0.0066933	-0.0055121	-0.0061189
	-0.0044	-0.004724	-0.002952941	-0.0044115
	-0.0035	-0.0037	-0.0030378	-0.00309
	0.0042	0.002362	0.004921	0.0033259
	0.0082	0.0072244	0.0096462	0.00708705
	0.0144	0.012362	0.015945	0.013474
	0.0211	0.019095	0.022245	0.018977



Skala	$V_r = V_I$ (V)	V_s (V)		
		min	mak	rata
2	-5	-4.48291	-4.64596	-4.48291
	-4.5	-4.2128	-3.9766	-4.03797
	-4	-3.7797	-3.5435	-3.59889
	-3.5	-3.19888	-3.071	-3.1314
	-3	-2.8747	-2.26379	-2.707
	-2.51	-2.44109	-2.20486	-2.26828
	2.505	2.6473	2.36233	2.21676
	3	2.51984	2.7954	2.659142
	3.495	2.9529	3.22854	3.09858
	4	3.42541	3.66164	3.5117
	4.5	3.9372	4.09474	3.99646
	5	4.33098	4.56721	4.44836



Skala	$V_r = V_t$ (V)	V_s (V)		
		min	mak	rata
1.	-19.915	-19.7259	-18.565	-17.5315
	-17.5	-16.5365	-14.5678	-15.2851
	-15.02	-14.567841	12.59921	-13.10281
	-12.495	-12.59921	-10.23686	-11.01088
	-10.04	-10.23686	-7.874509	-8.806
	-7.495	-7.8745	-5.9658	-6.59871
	-5.005	-5.9058	-3.5435	-4.39141
	5.02	3.14298031	5.11843	4.617881
	7.5	5.51215	7.48078	6.7645
	10	7.874509	9.84613	8.96045
	12.5	9.8431	12.2055	11.26055
	15	12.2055	14.17411	13.4294
	17.49	14.7259	16.5365	15.6196
	19.74	18.505	19.7259	17.5315



Lampiran 3 : Ralat pada tiap skala


Skala	Range tegangan (V)	Ralat (V)
0	1000	3.921568627
1	40	0.156862745
2	10	0.039215666
3	5	0.019607843
4	0.5	0.001960784
5	0.05	0.000196078
6	0.005	1.96078E-05



Lampiran 4 : Uji linieritas tegangan

V_r (V)	V_l (V)
-19	-16.77671
-9.97	-9.9205897
-4	-3.992832792
-3	-2.998307
-2	-2.00179092
-1.003	-0.96791
-0.203	-0.20298152
-0.1057	-0.106255
-0.0207	-0.02114929
-0.01	-0.010112324
0.0104	0.010701329
0.02	0.020072679
0.0994	0.098927446
0.199	0.199078473
1.005	0.9987224
2	2.04845
3	3.01133
4.01	4.009142
10	9.756
19	18.542887






Lampiran 5 : Data frekuensi untuk dilinierisasi.

No.	$f_r = f_l$ (Hz)	f_s (Hz)		
		min	mak	rata-rata
1	25.0085	3.70E-03	3.72E-03	3.71E-03
2	30.0035	4.42E-03	4.57E-03	4.46E-03
3	40.009	5.81E-03	6.13E-03	5.98E-03
4	50	7.30E-03	7.52E-03	7.42E-03
5	60.004	8.77E-03	9.69E-03	8.91E-03
6	70.062	1.00E-02	1.08E-02	1.08E-02
7	80.095	1.16E-02	1.23E-02	1.19E-02
8	90.19	1.30E-02	1.39E-02	1.34E-02
9	100.01	1.41E-02	1.61E-02	1.49E-02
10	125.03	1.79E-02	1.96E-02	1.86E-02
11	150.002	2.08E-02	2.56E-02	2.23E-02
12	175.02	2.44E-02	2.86E-02	2.60E-02
13	200.04	1.47E-02	3.45E-02	2.96E-02
14	225.03	1.67E-02	3.31E-02	3.31E-02
15	250.03	1.82E-02	4.55E-02	3.69E-02




Lampiran 6 : Uji frekuensi linier

f_r (Hz)	f_l (Hz)
25	24.71252
50.3	49.91658
100.032	100.0325
150.01	150.7927
200	200.1762
250.07	250.4606




Lampiran 7 : Hasil tampilan gerigi



Tegangan Mak(Vdc)	9.3386059346E-01	Frekuensi Mak	4.8959220807E+01
Tegangan Min.	-1.1633970543E+00	Frekuensi Min.	5.1623976522E+01
Tegangan rata-rata(ac)	-1.1574487157E-01	Frekuensi rata-rata.	4.9872617134E+01
TegDC rata-rata.	-7.9646516293E-02	Periode Mak	2.0425161666E-02
Tegangan efektif	6.2670813170E-01	Periode Min.	1.9970844080E-02
		Periode rata-rata	2.0051083289E-02



Lampiran 8 : Hasil tampilan gelombang kotak



Tegangan Mak<dc>	1.0359412674E+00	Frekuensi Mak	9.7730318866E+01
Tegangan Min	-1.3109628306E+00	Frekuensi Min	1.0219665602E+02
Tegangan_rata-rata(ac)	-1.3825131468E-01	Frekuensi_rata-rata	1.0014331427E+02
TegDC_rata-rata	-4.2276119651E-02	Periode Mak	1.0232239203E-02
Tegangan_efektif	1.1390928169E+00	Periode Min	9.7850559788E-03
		Periode_rata-rata	9.9956990828E-03

